

12V,24 ALUMINIJ IP67

Power supply constant voltage

EN: LED power supply constant voltage



INDEX	 IN	 OUT					 L x W x H	
007921	100-240VAC	12VDC	1A	12W	100mVpp	-30°C ÷ +45°C	76x37x28mm	5902216703247
126	85-264VAC	12VDC	1,1A	15W	100mVpp	-30°C ÷ +45°C	132x30x20mm	5902216703278
123	170-264VAC	12VDC	1,5A	20W	80mVpp	-30°C ÷ +45°C	143x30x20mm	5902216703285
1188	170-264VAC	12VDC	2,5A	30W	100mVpp	-30°C ÷ +45°C	220x30x20mm	5902216703308
008911	100-240VAC	12VDC	3A	36W	100mVpp	-30°C ÷ +45°C	200x30x20mm	5902216717978
1181	85-264VAC	12VDC	3,75A	45W	100mVpp	-30°C ÷ +45°C	210x29x21mm	5902216703322
1164	170-264VAC	12VDC	5,0A	60W	80mVpp	-30°C ÷ +45°C	178x68x50mm	5902216703339
013381	230 VAC	12VDC	6,67A	80W	80mVpp	-30°C ÷ +45°C	160x51x32 mm	5902808801559
111	170-264VAC	12VDC	8,5A	100W	80mVpp	-30°C ÷ +45°C	206x130x65mm	5902216703353
1101	170-264VAC	12VDC	12,5A	150W	120mVpp	-30°C ÷ +45°C	235x120x55mm	5902216703506
1085	170-264VAC	12VDC	16,67A	200W	120mVpp	-30°C ÷ +45°C	265x70x55mm	5902216718029
008514	170-264VAC	12VDC	20,83A	250W	180mVpp	-30°C ÷ +45°C	230x120x56mm	5902216703513
003178	185~265VAC	12VDC	12,5A	150W	120mVpp	-30°C ÷ +45°C	120x55x183mm	5902216717985
009754	100-240VAC	12VDC	12,5A	150W	120mVpp	-30°C ÷ +45°C	120x55x183mm	5902216703360
004062	185-265VAC	12VDC	16,7A	200W	120mVpp	-30°C ÷ +45°C	205x120x55mm	5902216720541
008060	185-240VAC	12VDC	20A	240W	180mVpp	-30°C ÷ +45°C	246x66x42mm	5902216720558
1052	170-250VAC	24VDC	2,5A	60W	80mVpp	-30°C ÷ +45°C	178x68x50mm	5902216703520
1054	170-250VAC	24VDC	4,5A	100W	80mVpp	-30°C ÷ +45°C	206x130x65mm	5902216703537
008058	100-240VAC	24VDC	4,2A	100W	80mVpp	-30°C ÷ +45°C	153x88x47mm	5902216747227
046400	100-265 VAC	24VDC	6,25A	150W			225x52x23mm	5902808813859
007150	170-250VAC	24VDC	8,33A	200W	120mVpp	-30°C ÷ +45°C	230x120x56mm	5902216718012

IP 
67 IN&OUT



Materiał / Materiál / Materiál

PL: aluminium

CZ: hliník

SK: hliník

EN: aluminum