

NAPAJANJE

DC NAPAJANJE

CZ: Napájecí zdroje s konstantním proudem/ SK: Napájacie zdroje s konštantným prúdom/ EN: LED power supply constant current



INDEX	 IN	 OUT				 L x W x H	
4549	230 V AC	12 V DC	3 A	36 W	0°C ÷ +45°	200x100x45	5902216703186
4528	230 V AC	12 V DC	3,75	45 W	0°C ÷ +45°	110x78x36	5902808805755
4537	230 V AC	12 V DC	5 A	60 W	0°C ÷ +45°	110x80x40	5902216703193
010848	230 V AC	12 V DC	16,5 A	200 W	0°C ÷ +45°	199x98x43	5902216703230
000007	230 V AC	12 V DC	25 A	300 W	0°C ÷ +45°	198x109x50	5902216716513
4533	230 V AC	12 V DC	33 A	400 W	0°C ÷ +45°	215x113x50	5902216721227
003581	230 V AC	12 V DC	40 A	500 W	0°C ÷ +45°	211x114x50	5902216721210
1014	230 V AC	24 V DC	2,5 A	60 W	0°C ÷ +45°	110x78x36	5902216703476
258	230 V AC	24 V DC	16,5 A	400 W	0°C ÷ +45°	215x114x50	5902216724433
6559	230 V AC	24 V DC	20 A	500 W	0°C ÷ +45°	238x124x65	5902216703391

IP



20

IN



Materiál / Materiál / Material

PL: Tworzywo sztuczne

CZ: Plast

SK: Plast

EN: Plastic