

Solar flood light

98SOL307 98SOL308

GENERAL INFORMATION »

- ∴ Flood light power: 10W ,30W
 - ∴ LED & Lens: LM-80 LEDs: 2835SMD; high transmittance PC optical lens
 - ∴ Battery: 3.7V/3600mAh, 6.4V/6000mAh Li-ion battery
 - ∴ Charging time: 8h
 - ∴ Discharging time:
 - Mode A: till 3 nights
 - Mode B: till 2 nights
 - ∴ Material: ABS + PC
 - ∴ Colour body: Black
 - ∴ Protection against dust and moisture: IP65
 - ∴ Sensor specification:
 - Detection range: 120°
 - Detection distance: 6m
 - Installation height: ≤ 4meters
 - ∴ Functions:
 - A- Full brightness 30 or 100%
 - B- continuously full brightness.
- After 5h 30% brightness after motion detection and 5% when 20sec no motion
Cable length from the panel to the floodlight: 5M

FEATURES »

- ∴ High quality, integrated flexible and outstanding design
- ∴ Durable & Waterproof
- ∴ Solar power supply and environment-friendly
- ∴ Energy-saving- ZERO electricity cost.
- ∴ No wiring needed and easy to install.
- ∴ One sensor inductive, wider detection angle, higher sensitivity.
- ∴ Applications: all the area inconvenient in electricity but full of sunshine, such as gardens, billboard, buildings, parking lot, entrance, courtyard, road, street, hotel etc



TECHNICAL SPECIFICATION SHEET

PRODUCT DETAILS »

Catalogue number	Power Flood light (W)	Whole fixtures lumens (lm)	Efficiency	Colour	Battery (V/mAh)
98SOL307	10	1300	130lm/W	Black	3.7V/ 3600mAh
98SOL308	30	4500	150lm/W	Black	6.4V/ 6000mAh

DIMENSION »

Catalog number	Dimension Width x Height(mm)
98SOL307	153x144
98SOL308	253x220



ADDITIONAL INFORMATION »

Catalogue number	Packing/Box (pcs)
98SOL307	1
98SOL308	1

